Supergen Engine Oils, a range of automotive lubricants, are proudly manufactured in India. Exceptional quality and economically priced, Supergen Engine Oils are available in Mineral Base, Premium Mineral, Semi-Synthetic and Premium Synthetic variants.

Engineered to cater to the needs of various vehicles like motorcycles, cars, trucks, tractors, earthmovers along with gen-sets.

Supergen is here for the ones who aspire to excel. Gear up, rise, let Supergen energize your engines.

# 

Engine Oils

• SUPERGEN

# DESCRIPTION

Supergen 5W20 provides high temperature stability, which ensures reliable protection under challenging conditions. Its high engine performance characteristics lead to optimal power delivery, and its improved fuel economy contributes to cost savings and reduced environmental impact. By selecting Supergen 5W20, users can expect smoother engine operation, enhanced acceleration, improved fuel efficiency, and extended engine longevity, making it a valuable choice for vehicles that seek a balance between performance, efficiency, and sustainability.

## **APPLICATIONS**

Primarily used in cars with petrol and diesel engines for enhanced fuel efficiency and cold weather protection.

## **ADVANTAGES**

- Lubrication: Reduces friction between engine parts, ensuring smooth operation and minimizing wear.
- Cleaning and Protection: Contains additives that prevent the build-up of sludge, varnish, and deposits while protecting against corrosion.
- **Fuel Efficiency:** Improves fuel economy by reducing friction and optimizing engine performance.
- **Noise Reduction:** Dampens noise generated by moving parts, resulting in a quieter driving experience.
- Extended Engine Life: Provides essential lubrication, protection, and cleaning to extend the overall lifespan of the engine.
- Wear Prevention: Minimizes wear and tear on engine components, reducing the need for repairs.
- Oxidation and Thermal Stability: Resists oxidation and maintains stability at high temperatures for long-lasting performance.
- Compatibility with Modern Engine Technologies: Formulated to meet the requirements of advanced engine technologies.
- Extended Oil Change Intervals: Technological advancements allow for longer oil change intervals, reducing maintenance frequency.
- Improved Cold Weather Performance: Maintains viscosity control in cold climates, ensuring efficient lubrication and protection.

#### **TYPES**

#### Mineral, Premium Mineral, Semi-Synthetic & Premium Synthetic Base

|  | Base                                      | Specifications | Performance Claims                   | Appearance    | Density<br>@<br>29°C | Viscosity<br>at 40°C | Viscosity<br>at 100°C | VI  | Flash<br>Point<br>°C | Pour<br>Point<br>°C | Vehicle Type/<br>Application |
|--|---|----------------|--------------------------------------|---------------|----------------------|----------------------|-----------------------|-----|----------------------|---------------------|------------------------------|
| SUPERGEN<br>5W20<br>PETROL /<br>DIESEL | Mineral<br><b>(SILVER)</b>                | API SL/CI-4    | ACEA A3/B4-16,<br>MB 229.1, JASO DH1 | Light Brown   | 0.85-0.90            | 50-60                | 8.1                   | 130 | 200                  | (-)20               | Cars                         |
|  | Premium<br>Mineral<br><b>(SILVER+)</b>    | API SN/CI-4+   | ACEA A3/B4-16,<br>MB 229.1, JASO DH1 | Light Brown   | 0.85-0.90            | 50-60                | 8.1                   | 130 | 200                  | (-)20               | Cars                         |
|  | Semi<br>Synthetic<br><b>(GOLD)</b>        | API SL/CI-4    | ACEA A3/B4-16,<br>MB 229.1, JASO DH1 | Light Brown   | 0.85-0.90            | 40-50                | 8.1                   | 145 | 210                  | (-)25               | Cars                         |
|  | Premium<br>Synthetic<br><b>(PLATINUM)</b> | API SN/CI-4+   | ACEA A3/B4-16,<br>MB 229.1, JASO DH1 | Golden Yellow | 0.80-0.85            | 40-50                | 8.1                   | 170 | 220                  | (-)40               | Cars                         |

#### **STORAGE**

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

