

Supergen Engine Oils, a range of automotive lubricants, are proudly manufactured in India. Exceptional quality and economically priced, Supergen Engine Oils are available in Mineral Base, Premium Mineral, Semi-Synthetic and Premium Synthetic variants.

Engineered to cater to the needs of various vehicles like motorcycles, cars, trucks, tractors, earthmovers along with gen-sets.

Supergen is here for the ones who aspire to excel. Gear up, rise, let Supergen energize your engines.



DESCRIPTION

Supergen ATF offers significant benefits that enhance the performance and longevity of automatic transmissions. Its high-temperature protection guards against fluid degradation and wear, its outstanding frictional characteristics optimize gear shifts and reduce wear, and its thermal stability ensures reliable operation across temperature variations. Opting for Supergen ATF translates to smoother gear shifts, reduced risk of transmission overheating, and extended transmission life, making it a valuable choice for maintaining the optimal performance of automatic transmissions.

APPLICATIONS

ATF stands for Automatic Transmission Fluid. This oil is designed for automatic transmissions and hydraulic systems in vehicles. It provides smooth shifting, protects against wear, and maintains proper hydraulic pressure in the transmission.

ADVANTAGES

- ATF oils boost engine response, delivering smoother acceleration.
- Reliable lubrication even in high temperatures for consistent performance.
- Detergents in ATF oils prevent deposits and maintain cleanliness.
- Withstands heat breakdown, preserving effectiveness.
- Fluidity in low temps ensures quick, smooth starts.
- Designed for modern engines with advanced features.
- Optimized performance contributes to lower emissions.

TYPES

Mineral, Premium Synthetic Base

	Base	Specifications	Performance Claims	Appearance	Density @ 29°C	Viscosity at 40°C	Viscosity at 100°C	VI	Flash Point °C	Pour Point °C	Vehicle Type/ Application
SUPERGEN ATF I	Mineral (SILVER)	ATF	General Motors Type A Suffix A	Light Brown	0.85-0.90	38-42	7.2	150	200	(-)20	Automatic Transmissions
SUPERGEN ATF XI	Premium Synthetic (PLATINUM)	ATF	Dexron III(G)	Golden Yellow	0.80-0.85	33-37	7.2	170	220	(-)40	Automatic Transmissions

STORAGE

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60 °C, exposed to hot sun or freezing conditions.

