SUPERGEN STOU PREMIUM SAE 15W30



Supergen Engine Oils, a range of automotive lubricants, are proudly manufactured in India. Exceptional quality and economically priced, Supergen Engine Oils are available in Mineral Base, Premium Mineral, Semi-Synthetic and Premium Synthetic variants.

Engineered to cater to the needs of various vehicles like motorcycles, cars, trucks, tractors, earthmovers along with gen-sets.

Supergen is here for the ones who aspire to excel. Gear up, rise, let Supergen energize your engines.



DESCRIPTION

Supergen STOU PREMIUM SAE 15W30's ability to provide good lubrication at low temperatures due to its "15W" winter viscosity rating contributes to its exceptional cold-starting abilities. The oil can flow more readily through the engine, ensuring that critical components are properly lubricated from the moment the engine is started, which in turn reduces wear and tear during startup. The detergent properties of this oil help to dissolve and remove existing deposits, keeping the engine and components clean. By ensuring a clean internal environment, Supergen STOU SAE 15W30 optimizes combustion, reduces wear, and maintains engine efficiency Additionally, Supergen STOU PREMIUM SAE 15W30 is designed to exhibit excellent viscosity-temperature behavior. The "15W30" in its name signifies its viscosity rating at different temperatures.

APPLICATIONS

STOU stands for Super Tractor Oil Universal, and SAE 15W30 indicates its viscosity grade. This oil is multipurpose and can be used in tractor transmissions, hydraulics, and final drives. It is well-suited for modern agricultural machinery.

ADVANTAGES

- Tractor Transmission Oil ensures seamless gear shifts for uninterrupted tractor operation.
- It boosts power output while maintaining fuel efficiency, optimizing tractor performance.
- The oil minimizes friction between parts, extending their lifespan and reducing wear and tear.
- It prevents overheating by efficiently dissipating heat, safeguarding the transmission system.
- The oil's additives protect against rust and corrosion, enhancing component durability.

TYPES

Premium Synthetic Base

	Base	Specifications	Performance Claims	Appearance	Density @ 29°C	Viscosity at 40°C	Viscosity at 100°C	VI	Flash Point °C	Pour Point °C	Vehicle Type/ Application
SUPERGEN STOU PREMIUM SAE 15W30	Premium Synthetic (PLATINUM)	STOU	API CE/SF, US MIL-L-2104D, ACEA E-3, Massey Ferguson : M 1139, CMS 1135, Ford : M2C 159B & 159C & M2C 134D, ZF : TE ML 07	Golden Yellow	0.80-0.85	60-65	10.5	160	220	(-)40	Super Tractor Oil Universal

STORAGE

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60°C, exposed to hot sun or freezing conditions.

