

Supergen Engine Oils, a range of automotive lubricants, are proudly manufactured in India. Exceptional quality and economically priced, Supergen Engine Oils are available in Mineral Base, Premium Mineral, Semi-Synthetic and Premium Synthetic variants.

Engineered to cater to the needs of various vehicles like motorcycles, cars, trucks, tractors, earthmovers along with gen-sets.

Supergen is here for the ones who aspire to excel. Gear up, rise, let Supergen energize your engines.



DESCRIPTION

Supergen UTTO is engineered to provide balanced lubricity, a crucial factor in optimizing the performance of transmissions and hydraulic systems. Supergen UTTO's formulation is carefully designed to strike the right balance between reducing friction and ensuring proper lubrication in both transmission and hydraulic components. Supergen UTTO incorporates advanced additives that create a protective barrier on metal surfaces, preventing the interaction between corrosive agents and the metal. This barrier effectively inhibits rust formation and corrosion, enhancing the durability and reliability of the systems. Supergen UTTO is designed with improved oxidation resistance, which is crucial for maintaining the effectiveness of the lubricant over time.

APPLICATIONS

This is specialized oil designed for use in tractor transmissions, hydraulic systems, and wet brakes. It offers excellent frictional characteristics, anti-wear properties, and oxidation stability, making it suitable for various agricultural equipments.

ADVANTAGES

- Tractor Transmission Oil ensures seamless gear shifts for uninterrupted tractor operation.
- It boosts power output while maintaining fuel efficiency, optimizing tractor performance.
- The oil minimizes friction between parts, extending their lifespan and reducing wear and tear.
- It prevents overheating by efficiently dissipating heat, safeguarding the transmission system.
- The oil's additives protect against rust and corrosion, enhancing component durability.

TYPES

Mineral, Premium Synthetic Base

	Base	Specifications	Performance Claims	Appearance	Density @ 29°C	Viscosity at 40°C	Viscosity at 100°C	VI	Flash Point °C	Pour Point °C	Vehicle Type/ Application
SUPERGEN UTTO	Mineral (SILVER)	Wet Brake Oil	Ford New Holland - M2C 134 D, Massey Ferguson - M1135 & M1141, John Deere - J 20 C, J 14 A, J 20 D, Allison - C4, Denison - HF-0, HF-1, HF-2	Light Brown	0.85-0.90	70-80	10.9	130	200	(-)20	Tractor Transmissions
SUPERGEN UTTO PREMIUM	Premium Synthetic (PLATINUM)	Wet Brake Oil	Ford New Holland - M2C 134 D, Massey Ferguson - M1135 & M1141, John Deere - J 20 C, J 14 A, J 20 D, Allison - C4, Denison - HF - 0,1,2	Golden Yellow	0.80-0.85	60-65	10.5	160	220	(-)40	Tractor Transmissions

STORAGE

All packages should be stored under cover. Where outside storage is unavoidable drums should be laid horizontally to avoid the possible ingress of water and damage to drum markings. Products should not be stored above 60 °C, exposed to hot sun or freezing conditions.

